



Model	25K				30K				40K			
Grid	L-N/PE	L1/L2/L3	L-N/PE	L1/L2/L3	L-N/PE	L1/L2/L3	L-N/PE	L1/L2/L3	L-N/PE	L1/L2/L3	L-N/PE	L1/L2/L3
Parameter	Duration (ms)		Value (A)		Duration (ms)		Value (A)		Duration (ms)		Value (A)	
Peak Short circuit current	3	2	71.2	96.3	3	2	73.4	97.5	3	3	68.5	98.7
Peak 1 Cycle RMS current	20	20	49.5	61.7	20	20	51.7	62.4	20	20	54.5	67.6

Model	50K				60K				125K			
Grid	L-N/PE	L1/L2/L3	L-N/PE	L1/L2/L3	L-N/PE	L1/L2/L3	L-N/PE	L1/L2/L3	L-N/PE	L1/L2/L3	L-N/PE	L1/L2/L3
Parameter	Duration (ms)		Value (A)		Duration (ms)		Value (A)		Duration (ms)		Value (A)	
Peak Short circuit current	3	3	94.6	121.8	3	3	105.4	142.5	3	3	163.2	223.1
Peak 1 Cycle RMS current	20	20	69.8	75.6	20	20	79.2	85.3	20	20	133.1	156.6